

Technical Data Sheet

SYNTHETIC RUBBER ADHESIVE SR-555

DESCRIPTION

SR-555 is a solvent borne, synthetic rubber based adhesive.

MATERIAL BONDED/APPLICATIONS

SR-555 is a general purpose adhesive It binds a variety of porous and non-porous surfaces including, PVC cloth, natural and polychloroprene rubber, hard boards, wood metal and painted surfaces.

BINDING INSTRUCTIONS

- 1. Prepare the surfaces to be bonded by roughing or cleaning as required
- 2. Applications of adhesives can be carried out by brush, scraper or press equipment.
- 3. Allow adequate drying time. Bring the two surfaces together using as much pressure as possible.

TYPICAL ADHESIVE CHARACTERS

Physical form : Mobile brushable liquid
Color : Translucent light brown
Odor : Predominantly Hydrocarbon

Chemical type : Polychloroprene Rubber/Synthetic Resin Solvent : Mixture of aromatic solvent & petroleum spirit

Viscosity : 14 poise approx. Specific gravity : 0.84 approx.

Flammability : Highly inflammable Packaging : 1ltr.,5ltr., & 25ltrs.

Storage : Store under dry conditions and in shade
Shelf life : One year from the date of manufacture under

the above conditions of storage.

/Continued 2...

MATERIAL SAFETY DATA

Material safety Data sheet(MSDS) will be available on request.

STORAGE:

Store under dry conditions and in shade and away from any direct sunlight.

SHELF LIFE

One year from the date of manufacture under the recommended conditions of storage.

Bostik India Private Limited
An Arkema Company

www.bostik.com

Our Authorized Distributors



No 475–F2, Sourabha, Jawaharlal Nehru Road, BEML 3rd Stage, Opp Sub Register Office, RR Nagar, Bangalore, Karnataka, India – 560098

Landline: 080-28611303 / 28601393 Phone: +919538101456 / 9538501236

Mail: info@durgamba.co.in Web: www.durgamba.co.in