

## Technical Data Sheet

---

# SEALER COAT

## Acrylic Penetrating Primer Coating

---

### DESCRIPTION

Bostik Sealer Coat is water-based primer composed of acrylic emulsion polymer, properly selected white pigments and additives in water as a medium. It is used as primer over exterior and interior building walls before application of Bostik Elastocoat and Bostik Exterior Coat and other water based paints.

### AREAS OF APPLICATION

It is an ideal material recommended for  
RCC Structure  
Masonry Walls  
Sloping /Flat Roofs  
Cooling Tower  
Bridges

### ADVANTAGES

Waterborne product , Eco-friendly  
Single component , ease of application  
Provides deep penetration thus imparts excellent substrate adhesion.  
Used as a primer on internal and external surfaces.  
Long term exterior durability

### PROPERTIES

Type	Single pack
Colour	White
Consistency	Dilutable with potable water ( 10% by volume )
Density @ 25°C, g/cc	1.03 ± 0.10
Surface dry time	30 minutes
Adhesion on concrete	Excellent
Coating interval	2 - 3 hrs at 30°C
Weather Resistant	Excellent

### APPLICATION INSTRUCTIONS

#### SURFACE PREPARATION

Concrete surfaces should be free from laitance, impurities and dust.  
The pre-requisites for good adhesion of the coating are cleanliness of the surface. Unless these are ensured by proper surface preparation, a successful performance can not be guaranteed.



## **APPLICATION**

Any deficiencies on the surface should be rectified before applying Bostik Sealer coat  
Dilute Sealer coat up to 10 % by volume with potable water  
Apply Sealer coat for better adhesion and sealing  
Allow the sealer coat to dry for 2 hours

## **CLEANING**

Water based product.  
Hence ease of cleaning all tools by soap water followed by plain water.

## **COVERAGE**

Bostik Sealer coat :12 sq.m /ltr/coat

Actual coverage depends on application techniques, ambient conditions, wastage, surface condition etc.

## **PACKING**

Bostik Sealer coat :1 & 5 Ltrs

## **STORAGE & SHELF LIFE:**

Sealer Coat as supplied shall be stored in a cool and dry place away from sunlight, moisture and high humidity and have a shelf life of 12 Months in the original sealed packing.

## **HEALTH & SAFETY:**

Sealer Coat is water borne primer and eco-friendly. It is not health hazardous.

## **WARRANTY**

Whilst Bostik India Pvt Ltd., strives to ensure that any advice, information or recommendation given are appropriate and correct, it cannot accept any liability directly or indirectly arising out of the use of the product, since the method and place of application of the products are beyond their control. Its guarantee is therefore limited to The quality of materials delivered.

---

## Our Authorized Distributors



No 475-F2, Sourabha, Jawaharlal Nehru Road,  
BEML 3rd Stage, Opp Sub Register Office, RR Nagar,  
Bangalore, Karnataka, India – 560098

**Landline : 080-28611303 / 28601393**  
**Phone : +919538101456 / 9538501236**

Mail : [info@durgamba.co.in](mailto:info@durgamba.co.in)  
Web: [www.durgamba.co.in](http://www.durgamba.co.in)

---