



Technical Data Sheet

ELASTOCOAT

High Performance Acrylic Elastomeric Coating

DESCRIPTION

Bostik Elastocoat is a high performance Elastomeric acrylic based water proofing coating with antifungal and crack bridging ability. Recommended for protection of exterior cementitious surfaces

AREAS OF APPLICATION

It is an ideal material recommended for
RCC Structure
Masonry Walls
Sloping /Flat Roofs
Cooling Tower
Bridges

ADVANTAGES

Waterborne product , Eco-friendly
Single component , ease of application
Tint able white base
Excellent antifungal & antibacterial properties
Low water absorption
Seamless membrane with good breath ability
Reliable crack bridging
Low dirt pick up
Long term exterior durability
UV stable

PROPERTIES

Type	Single pack
Colour	Generally white , but tintable
Consistency	Dilutable with potable water (10% by volume)
Surface dry time	30 minutes
Adhesion on concrete	Excellent
Recoating interval	4-5 hrs at 30°C
Elongation @ 150 micron DFT	Minimum 150%
Crack bridging	0.5 mm



APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Concrete surfaces should be free from laitance , impurities and dust .
The pre-requisites for good adhesion of the coating are cleanliness of the surface. Unless these are ensured by proper surface preparation, a successful performance can not be guaranteed.

APPLICATION

Any deficiencies on the surface should be rectified before applying Bostik Sealer coat
Dilute Sealer coat up to 10 % by volume with potable water
Apply Sealer coat for better adhesion and sealing
Allow the sealer coat to dry for 2 hours
Dilute Bostik Elastocoat 20% by volume with potable water
Apply first coat Bostik Elastocoat by roller or brush on the primed surface
Allow drying for 4-5 hours before application of second coat

CLEANING

Water based product .
Hence ease of cleaning all tools by soap water followed by plain water.

COVERAGE

Bostik Sealer coat : 12 sq.m /ltr/coat
Bostik Elastocoat : 3.5 sq.m /ltr/2coat

Actual coverage depends on application techniques, ambient conditions, wastage, surface condition etc.

PACKING

Bostik Sealer coat : 1 & 5 Ltrs
Bostik Elastocoat : 5 & 20 Ltrs

STORAGE & SHELF LIFE:

Elastocoat as supplied shall be stored in a cool and dry place away from sunlight, moisture and high humidity and have a shelf life of 12 Months in the original sealed packing.



HEALTH & SAFETY:

Elastocoat is water borne paint & eco-friendly. It is not health hazardous.

WARRANTY

Whilst Bostik India Pvt Ltd., strives to ensure that any advice, information or recommendation given are appropriate and correct, it cannot accept any liability directly or indirectly arising out of the use of the product, since the method and place of application of the products are beyond their control. Its guarantee is therefore limited to the quality of materials delivered.

Our Authorized Distributors



No 475-F2, Sourabha, Jawaharlal Nehru Road,
BEML 3rd Stage, Opp Sub Register Office, RR Nagar,
Bangalore, Karnataka, India – 560098

Landline : 080-28611303 / 28601393
Phone : +919538101456 / 9538501236

Mail : info@durgamba.co.in
Web: www.durgamba.co.in
