



Glazing Silicone

GENERAL PURPOSE SILICONE SEALANT



DESCRIPTION

Glazing Silicone is a high performance, acetic (acetoxo) cure, ultraviolet resistant one component silicone sealant. Bostik Glazing Silicone is an industrial grade, acetic cure sealant designed specifically for Sealing and waterproofing all types of windows and frames, ideally used for glass and glazing.

RECOMMENDED USES

- In construction of shop front windows
- Installation of aluminium windows between glass and aluminium
- Sealing around skylights and light fittings
- Construction of glass display cabinets
- Sealing of glass blocks and some plastics
- Fish Aquariums

FEATURES & BENEFITS

- UV light resistant
- Waterproof
- Suitable for interior and exterior applications
- Highly flexible
- Permanently elastic

PAINTABILITY

Non-paintable

COVERAGE

Approximately 11 linear metres per 280 gms. cartridge based on average joint size of 5 mm depth and 5 mm width.

PERFORMANCE PROPERTIES

Typical properties after 7 days cure at 25°C and 50% RH.

Tooling time (at 20°C)	3 - 5 minutes
Tack free time (Per Fed. Spec TTS001543A)	1 hour
Cure time (to 10mm depth @ 23°C & 50% RH)	5 - 7 days
Application range	10°C to 60°C
Temperature	- 62°C to + 177°C
Performance range Hardness shore A (ASTM D - 2440)	28
Tensile strength (ASTM D-412) 200	320 psi (23 kg /cm ²)
Sag, slump (Per TT - S - 001543A)	0.1
Specific gravity	1.05 approx
Cure method (Chemical type)	Acetoxo
UV and ozone resistance	Excellent
Joint movement	± 25%

PACKAGING

STOCK SIZE	COLOUR
GLAZING SILICONE	
280 gms. cartridge	Translucent
	Black
	White

STORAGE & SHELF LIFE

When stored at or below 30°C Bostik Glazing Silicone has a shelf life of 12 months from date of manufacture.

Our Authorized Distributors



No 475-F2, Sourabha, Jawaharlal Nehru Road,
BEML 3rd Stage, Opp Sub Register Office, RR Nagar,
Bangalore, Karnataka, India – 560098

Landline : 080-28611303 / 28601393
Phone : +919538101456 / 9538501236

Mail : info@durgamba.co.in
Web: www.durgamba.co.in